

You can rely on Rinnai

Represented By:

UNFLUED GAS HEATERS

RINNAI AVENGER 25

- Large heating capacity - up to 85sq.m or a volume of 204cu.m
- Rinnai peace of mind safety system: oxygen depletion, flame failure and tilt switch shut down systems
- Electronic ignition controls with a thermostat for accurate temperature control and a programmable clock timer for set and forget heating
- Quiet high performance filtered multi speed fan with air outlet at floor level provides rapid spread of warmth
- Convenient remote control operation



DIMENSIONS-

Height: 482mm
Width: 610mm
Depth: 239mm

LPG GAS CONSUMPTION:

Low: 0,13kg/hr
High: 0,54kg/hr

COLOURS:

White, Platinum Silver & Champagne



RINNAI ENDURO 13

- Medium heating capacity - up to 44sq.m or a volume of 106cu.m
- Rinnai peace of mind safety systems: oxygen depletion, flame failure and tilt switch shut down systems
- Electronic ignition controls with a thermostat for accurate temperature control and 24 hour delay timer
- Quiet high performance filtered multi speed fan with air outlet at floor level provides rapid spread of warmth



DIMENSIONS:

Height: 492mm
Width: 487mm
Depth: 243mm

LPG GAS CONSUMPTION:

Low: 0,09kg/hr
High: 0,28kg/hr

COLOURS:

White or Platinum Silver



IMPORTANT NOTE

These unflued Gas Heaters are not suitable for use in a bedroom & the room ventilation requirements as noted in the instruction/installation manual must be adhered to

VISIT OUR WEBSITE AT

www.macd.co.za

UNFLUED GAS HEATERS

RINNAI GRANADA 252

- Large heating capacity - up to 74sq.m or a volume of 178cu.m
- 3 heat settings and Radiant Burner with push button control and electronic ignition
- 2 speed circulating fan
- Rinnai peace of mind safety system: oxygen depletion, flame failure and tilt switch shut down systems



DIMENSIONS:

Height: 540 mm
Width: 620 mm
Depth: 220 mm

LPG GAS CONSUMPTION:

Low: 0,17 kg/hr
High: 0,51 kg/hr

COLOURS:

Off White or Platinum Silver



RINNAI INFINITY HOT WATER SYSTEMS



MODEL 20

Domestic applications
Flow rate: 2,7 to 24L/min
Output: 12L/m @ 40°C temperature rise
Preset Temperature Range: 55°C to 75°C
Minimum Water Pressure: 160Kpa
Maximum Gas Input:
160M J/Hr - 3,4 kg/hr LPG
Gas Type: LPG or NG
Electrical Consumption: 175W @ 230V
Features: Auto Ignition, Outlet Temperature Control, External Mounting with Power Flue Fan.

Dimensions:

H - 530mm
W - 350mm
D - 170mm

MODEL 26

Domestic & Light Commercial applications
Flow rate: 2,7 to 26L/min
Output: 16L/m @ 40°C temperature rise
Preset Temperature Range: 55°C to 85°C
Minimum Water Pressure: 170Kpa
Maximum Gas Input:
199M j/Hr - 4,3 kg/hr LPG
Gas Type: LPG or NG
Electrical Consumption: 175W @ 230V
Features: Auto Ignition, Outlet Temperature Control, Internal & external mounting models available with Power Flue Fan. Internal model requires balanced 90/120mm top Flue

Dimensions:

H - 600mm
W - 350mm
D - 224mm

MODEL 32

Heavy Duty Commercial applications
Flow rate: 2,7 to 32L/min
Output: 20L/m @ 40°C temperature rise
Preset Temperature Range: 55°C to 95°C
Minimum Water Pressure: 180Kpa
Maximum Gas Input:
250M j/Hr - 5,4 kg/hr LPG
Gas Type: LPG or NG
Electrical Consumption: 175W @ 230V
Features: Auto Ignition, Outlet Temperature Control, External Mounting with Power Flue Fan

Dimensions:

H - 600mm
W - 470mm
D - 220mm

J. MACDONALD & SONS cc IMPORTERS & DISTRIBUTORS

Tel: 021 696-7930

Tel: 011 886-9983

Email: richard@macd.co.za

Email: macdfirehouse@gmail.com